

Construction Alert

September 19, 2019

OC Public Works



Santa Ana River Flood Control Channel Maintenance/Excess Sand Removal

Project Summary

Removal of naturally accumulated sand in the area is performed 1-2 times per year, as routine maintenance, particularly before storm season (starting in October), to prevent potential water flow blockages.

WHERE

At the Santa Ana River flood control channel outlet between the cities of Huntington Beach and Newport Beach, west of Pacific Coast Highway.

* See other side for sand placement locations



WHAT

1. Approximately 70,000 cubic yards of accumulated sand will be removed from the channel outlet, as allowed through a regulatory permit for flood control maintenance. Removing the excess sand minimizes potential flood risks during rain events and also maintains the natural tidal flow with the adjacent Newport Shores marsh area.
2. Additionally, in coordination with the City of Newport Beach, crews will transport the removed sand to City beach areas that would benefit most from replenishment.

Your safety is the top priority! Large equipment will be used. Please observe all caution signs / barriers, and stay a safe distance from the work area.

WHEN

Anticipated Construction Duration:

September 23 — late November 2019

Equipment Operation:

Weekdays, 7:00 am — 3:30 pm

Crew members may be working on site 6:00 am—4:30 pm. Work schedule is tentative and subject to change.

CONTACT INFORMATION

  Shannon Widor, OCPW | 714.667.9759

 www.ocpublicworks.com

 ProjectInfo@ocpw.ocgov.com

 [Facebook.com/ocpublicworks](https://www.facebook.com/ocpublicworks)

 [Twitter.com/ocpublicworks](https://twitter.com/ocpublicworks)

Santa Ana River

Flood Control Channel Maintenance/Excess Sand Removal

Sand Placement Locations

 Potential sand replenishment areas:

- (1) between 52nd Street and 40th Street, and;
- (2) west of the Balboa Pier

